

Technical Data Sheet | Kitchen Tap

Carna Twin Lever Mono Kitchen Mixer 4E1436CO

> Specification Finish Dimensions Weight Body Spout Material Fittings Connection Cartridge Size Flow Restrictor Max Static Pressure

Issue No. v1 03 2024

Carna_4E1436CO_TDS_V1

www.instinctproducts.co.uk

411(h) x 47(w) x 186(d) mm

M10 - DN8 Flexible Hoses with 1⁄2″ BSP Thread Ends

16 Bar Min Operating Pressure 0.1 Bar Max Operating Pressure 6 Bar Max Water Temperature 60°C Flow Rates

No

Gunmetal

1.77kg

Brass

Brass

Easy Fix System

1⁄2″ QT Headwork

Pressure	0.2	0.5	1	3
Flow Straightener	4.0	7.9	12.8	24.5

All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance. Inclusion or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice.

186 5 MAX Ø35 ĥΛ 8 Key Features + Benefits **Certifications + Approvals** Fast 10 LP 圜 J ¢ **Fix**

kiw Flow Rate - 4.0 l/min ř2

Tested at 0.2 Bar

2201732 - Sept 25

StH Westco

Years Guarantee

Low Pressure

Flow

Straightener

Cold

Open

Fast

Fix

Flexible

Hose

Single Flow

Unit C6, William Way, Moss Industrial Estate, St Helens Road, Leigh, Lancashire, WN7 3PT. Technical Support – Tel: 01942 265311 Email: support@francistaps.co.uk All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.