

Helme Square Two Handle Twin Outlet Concealed Shower Valve INSHE1016, INSHE1017



Specification

Finish	Matt Black (INSHE1016) Brushed Brass (INSHE1017)
Dimensions	200(h) x 120(w) x 29-54(d) mm
Weight	2.44kg
Valve Body Material	Brass
Valve Connection	G½" Thread
Valve Handle Material	Zinc
Valve Plate	Stainless Steel
Min Operating Pressure	0.2 Bar
Max Operating Pressure	5 Bar
Max Static Pressure	-
Max Operating Temperature	-
Thermostatic Safety Stop Setting	38°C


Flow Rates

Pressure	0.2	0.5	1	3
L/min	3.8	10.5	14.6	22.9


All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance. Inclusion or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice.

Features

Dual Control	Flow and temperature are controlled separately giving accurate control of both
Safety	Automatic shut-off in the event of cold water supply failure, to prevent scalding



Key Features + Benefits



Certifications + Approvals

Flow Rate – 3.8 l/min

Tested at 0.2 Bar