

IN-100 Concentrate Corrosion Inhibitor
504223



Specification	
Bottle Colour Code	Yellow
Bottle Dimensions	137(h) x 72(w) x 49(d) mm
Bottle Volume	250ml
Bottle Weight	0.28kg
Liquid Colour	Dark Straw
Dosing Amount (No. of Rads / Volume)	10 / 100 litres
Shelf Life	Minimum 3 Years
Features	
Usage	Prevents corrosion, hard water limescale precipitation and is essential for protecting hot water heating systems and maintaining operational efficiency.
Dose Rate	Bottle contains 250ml. Minimum dosage to achieve the NSF CIAS performance specification is 250ml per 100 litres of system water (up to 10 radiators). Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Instinct chemicals.
Application	Dose via the feed and expansion tank or via a radiator as per BS7593:2019. Leave in System. For best results first flush system with IN-300 System Cleaner or IN-400 Sludge Remover.
Health & Safety	Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. Do not use with Primatic single feed cylinders. All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations. Installers must carry out all works in accordance with local regulations and bye-laws.

Key Features + Benefits

100 Litres

Treats up to 100 litres

10 Rads

Treats up to 10 Radiators

Prevents Scale + Corrosion

Non-Hazardous Formulation

250ml

Bottle Volume

Made from 50% Recycled Plastic

GB

Made in Great Britain

Certifications + Accreditations

NSF CIAS

Cert No. 2101/0419