

IN-100 Concentrate Corrosion Inhibitor 504223



Specification

Bottle Colour Code	Yellow
Bottle Dimensions	137(h) x 72(w) x 49(d) mm
Bottle Volume	250ml
Bottle Weight	0.28kg
Liquid Colour	Brown
Dosing Amount (No. of Rads / Volume)	10 / 100 litres
Shelf Life	Minimum 3 Years

Features

Usage	Prevents corrosion, hard water limescale precipitation and is essential for protecting hot water heating systems and maintaining operational efficiency.
Dose Rate	Bottle contains 250ml. Minimum dosage to achieve the NSF CIAS performance specification is 250ml per 100 litres of system water (up to 10 radiators). Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Instinct chemicals.
Application	Dose via the feed and expansion tank or via a radiator as per BS7593:2019. Leave in System. For best results first flush system with IN-300 System Cleaner or IN-400 Sludge Remover.
Health & Safety	Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. Do not use with Primatic single feed cylinders. All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations. Installers must carry out all works in accordance with local regulations and bye-laws.

Key Features + Benefits

100 Litres	10 Rads			250ml		GB
Treats up to 100 litres	Treats up to 10 Radiators	Prevents Scale + Corrosion	Non-Hazardous Formulation	Bottle Volume	Made from 50% Recycled Plastic	Made in Great Britain

Certifications + Accreditations



Scalemaster Ltd

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 0SR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.