INSTINCT®

Technical Data Sheet | Heating System Chemicals

www.instinctproducts.co.uk

IN-100 Corrosion Inhibitor (Contract Chemicals) 504582



Certifications + Accreditations

NSF NSF CIAS Cert No. 2409238

Scalemaster Ltd

Ā

Non-Hazardous

Prevents Non-Hazardou Scale + Corrosion Formulation

5L

Rottle

Volume

GB

Made in

Great Britain

2000

Litres

Treats up to 2000 litres

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 OSR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.

IN-100_504582_TDS_V3

INSTINCT®

Issue No. v3 10 2024

IN-100_504582_TDS_V3

www.instinctproducts.co.uk

Technical Data Sheet | Heating System Chemicals

IN-100 Corrosion Inhibitor (Contract Chemicals)

504582

Features

Dose Rate

Bottle contains 5 litres. Minimum dosage to achieve the NSF CIAS performance specification is 250ml per 100 litres of system water (up to 10 radiators). Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing of Instinct chemicals.

Application

Dose via the filling loop, feed and expansion tank or via any radiator or convenient filling point as per BS/7593:2006. Leave in the system. For best results first flush system with Instinct IN-300 System Cleaner or Instinct IN-400 Sludge Remover.

Protection

At final fill add Instinct IN-100 Inhibitor to prevent scale and corrosion.

Health & Safety

Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. **Do not use with PRIMATIC single feed cylinders.**

Scalemaster Ltd

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 OSR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.