

### IN-200 Concentrate Boiler Noise Silencer 504230



#### Specification

Bottle Colour Code	Red
Bottle Dimensions	137(h) x 72(w) x 49(d) mm
Bottle Volume	250ml
Bottle Weight	0.28kg
Liquid Colour	Clear
Dosing Amount (No. of Rads / Volume)	10 / 100 litres
Shelf Life	Minimum 3 Years

#### Features

Usage	For established central heating systems. Restores and maintains heat exchanger efficiency in hard water areas and stops boiler noise by re-dissolving limescale precipitation on heat exchanger surfaces.
Dose Rate	Bottle contains 250ml. This treats up to a 100 litre (10 radiators) system. Compatible with aluminium. No problems occur through overdosing (up to double dose) or mixing Instinct chemicals.
Application	To prevent 'kettling' and boiler noise. (First check noise is not caused by system design or mechanical fault before application). Dose via the feed and expansion tank or via a radiator as per BS7593:2019. <b>Leave in System.</b> For best results use with IN-100 Inhibitor.
Health & Safety	Keep out of reach of children. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. <b>Do not use with Primatic single feed cylinders.</b> All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations. Installers must carry out all works in accordance with local regulations and bye-laws.

#### Key Features + Benefits

<b>100</b> Litres	<b>10 Rads</b>			<b>250ml</b>		<b>GB</b>
Treats up to 100 Litres	Treats up to 10 Radiators	Dissolves Limescale	Non-Hazardous Formulation	Bottle Volume	Made from 50% Recycled Plastic	Made in Great Britain

#### Certifications + Accreditations

#### Scalemaster Ltd

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 0SR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.