

IN-500 Leak Sealer (Aerosol) 504537



Specification

Aerosol Colour Code	Green
Aerosol Dimensions	250(h) x 55(w) x 55(d) mm
Aerosol Volume	300ml
Aerosol Weight	0.42kg
Liquid Colour	Clear
Dosing Amount (No. of Rads / Volume)	12 / 120 litres
Shelf Life	Minimum 3 Years

Features

Usage	For the internal sealing of inaccessible leaks & weeping joints. Forms a soft seal within 24 hours. Will not cause blockages in circulatory pumps or air vents.
Dose Rate	Please see next page
Application	Please see next page
Warning	Please see next page
Health and Safety	Please see next page

Key Features + Benefits

120 Litres	12 Rads			24 hrs	GB
Treats up to 120 litres	Treats up to 12 Radiators	Seals Leaks + Weeping Joints	Non-Hazardous Formulation	Seals within 24 hrs	Made in Great Britain

Certifications + Accreditations

Scalemaster Ltd

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 0SR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.

IN-500 Leak Sealer (Aerosol) 504537

Features

Dose Rate

Can contains sufficient chemical to treat a 120 litre system (up to 12 radiators).

Application

Dose system via a convenient filling point-Registered design adapters are included for injection via a radiator bleed screw hole or ½" BSP fitting (e.g. radiator end plug or filling loop). Screw injector nozzle/connector into hole after isolating radiator, releasing pressure and removing bleed screw or end cap. (use cloth to avoid any spillage). Ensure tight fit and connect aerosol tube. Open 1 radiator valve, break off protective tab on top of can and inject whole contents. Close radiator valve. Carefully unscrew connector, replace bleed screw/end cap and open radiator valves. Forms a soft seal within 24 hours. Use with INSTINCT IN-100 Inhibitor. Will not cause blockages in circulatory pumps or air vents.

Warning

Pressurised container – May burst if heated Keep away from heat/sparks/open flames/hot surfaces and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.



Health & Safety

Contains gas under pressure – may explode if heated. Keep out of reach of children. Store in a well ventilated place. Dispose of contents & container in accordance with national regulations. Safety Data Sheet available upon request. **Do not use with PRIMATIC single feed cylinders.**