

IN-600 Concentrate Heat Optimiser 504278



Specification

Bottle Colour Code	Orange
Bottle Dimensions	137(h) x 72(w) x 49(d) mm
Bottle Volume	250ml
Bottle Weight	0.28kg
Liquid Colour	Clear
Dosing Amount (No. of Rads / Volume)	10 / 100 litres
Shelf Life	Minimum 3 Years

Features

Usage	Improves heat transfer. Saves up to 15% on heating costs.
Dose Rate	Minimum dosage is 250ml per 100 litre system capacity.
Application	Treat via a partially drained radiator or through the feed and expansion tank. Shake bottle and use entire contents. After treatment, bleed radiator to remove trapped air. Leave in system. Use with IN-100 Inhibitor.

Health & Safety



Danger – Contains wd-glucopyranose. Causes serious eye damage. Keep out of reach of children. Wear protective gloves/protective clothing/eye protection/face protection. **If in eyes** – Rinse cautiously with water for several minutes. remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison centre or doctor. Dispose of contents and container in accordance with national guidelines.

Do not use with Primatic single feed cylinders.

All Scalemaster® Heating System Chemicals are manufactured using non-hazardous formulations. Installers must carry out all works in accordance with local regulations and bye-laws.

Key Features + Benefits

100 Litres	10 Rads			250ml		GB
Treats up to 100 litres	Treats up to 10 Radiators	Improves Heat Transfer	Money Saving	Bottle Volume	Made from 50% Recycled Plastic	Made in Great Britain

Certifications + Accreditations

Scalemaster Ltd

Emerald Way, Stone Business Park, Stone, Staffordshire ST15 0SR. Technical Helpline: 01785 811636 Email: info@scalemaster.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.