

Instinct Pro UFH Blending Valve + Pump Pack (Wilco Pump) IN-2536J+WILO-PUMP



Blending Valve Specification

Finish	Chrome Plated
Dimensions	301(h) x 194.5(w) x 122(d) mm
Weight	1.87kg
Body Material	Nickel Plated Brass
Seals Material	EPDM
O-Rings Material	EPDM
Springs Material	Stainless Steel
Maximum Working Pressure	6 Bar (10 Bar for system testing)
Maximum Temperature Range	90°C
Adjustable Control Temperature Range	35 to 60°C
Thread Connections	BS EN ISO 228-1
Kv Value	2.8m ³ /h Dp = 1 Bar; Tmix = 45°C

Wilco Pump Specification

Finish	Composite Body / Grey
Dimensions	139(h) x 93.5(w) x 123(d) mm
Weight	-
Energy Efficiency Index (EEI)	≤ 0.20
Maximum Delivery Head	6.3m
Maximum Volume Flow	2.6m ³ /h

Features

Supplied with A rated 6m pump and 3/4" ball valves

The water supply temperature can be adjusted according to the structure of the floor

Designed for heat pump and low temperature systems that do require a thermostatic control valve

Key Features + Benefits

5	2			
Years Guarantee on Blending Valve	Years Guarantee on Wilco Pump	Pre Assembled	Temperature Gauge	Temperature Range

Certifications + Accreditations

Technical Data Sheet | Hydronic UFH

Instinct Pro UFH Blending Valve + Pump Pack (Wilco Pump) IN-2536J+WILO-PUMP

