

Ivelet Round Two Handle Twin Outlet Concealed Shower Valve INSIV1009, INSIV1010



Specification

| | |
|----------------------------------|---|
| Finish | Matt Black (INSIV1009) Brushed Brass (INSIV1010) |
| Dimensions | 200(h) x 120(w) x 29-54(d) mm |
| Weight | 2.44kg |
| Valve Body Material | Brass |
| Valve Connection | G½" Thread |
| Valve Handle Material | Zinc |
| Valve Plate | Stainless Steel |
| Min Operating Pressure | 0.2 Bar |
| Max Operating Pressure | 5 Bar |
| Max Static Pressure | - |
| Max Operating Temperature | - |
| Thermostatic Safety Stop Setting | 38°C |

Flow Rates


| Pressure | 0.2 | 0.5 | 1 | 3 |
|----------|-----|------|------|------|
| L/min | 3.8 | 10.5 | 14.6 | 22.9 |

All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance. Inclusion or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice.

Features

| | |
|--------------|---|
| Dual Control | Flow and temperature are controlled separately giving accurate control of both |
| Safety | Automatic shut-off in the event of cold water supply failure, to prevent scalding |

Key Features + Benefits



Aquadart Bathrooms Limited

Riverside Business Park, Royd Ings Avenue, Keighley, West Yorkshire BD21 4AF. Technical Support – Tel: 01535 613830 Email: sales@aquadart.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.

Certifications + Approvals

Flow Rate – 3.8 l/min

Tested at 0.2 Bar