

### Ivelet Round Three Handle Twin Outlet Concealed Shower Valve INSIV1011, INSIV1012



#### Specification

Finish	Matt Black (INSIV1011) Brushed Brass (INSIV1012)
Dimensions	280(h) x 120(w) x 29-54(d) mm
Weight	3.11 kg
Valve Body Material	Brass
Valve Connection	G½" Thread
Valve Handle Material	Zinc
Valve Plate	Stainless Steel
Min Operating Pressure	0.2 Bar
Max Operating Pressure	5 Bar
Max Static Pressure	-
Max Operating Temperature	-
Thermostatic Safety Stop Setting	38°C

#### Flow Rates


Pressure	0.2	0.5	1	3
L/min	4.0	6.3	9.1	15.8

All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance. Inclusion or restrictors (sold separately unless stated) will affect flow rate result. Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice.

#### Features

Dual Control	Flow and temperature are controlled separately giving accurate control of both
Safety	Automatic shut-off in the event of cold water supply failure, to prevent scalding

#### Key Features + Benefits



2  
Years  
Guarantee

LP  
Low  
Pressure

Anti  
Scald

#### Certifications + Approvals

Flow Rate – 4.0 l/min

Tested at 0.2 Bar

#### Aquadart Bathrooms Limited

Riverside Business Park, Royd Ings Avenue, Keighley, West Yorkshire BD21 4AF. Technical Support – Tel: 01535 613830 Email: sales@aquadart.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.