



Keros_INST13217BB_TDS_V1

Technical Data Sheet | Shower

www.instinctproducts.co.uk

Keros Thermostatic Twin Outlet Bar Shower Mixer INST13217BB



Specification			
Finish	Brushed Brass		
Dimensions	870-1200(h) x 307(w) mm		
Weight	3.7kg		
Body Material	Brass		
Hose Material	Smooth PVC		
Hose Length	1500mm		
Hose Connection	Nut / Cone		
Hose Bore	10mm		
Overhead	Adjustable		
Overhead Material	ABS		
Overhead Size	230mm		
Shower Arm Length	345mm		
Handset Material	ABS		
Handset Functions	Three		
Handset Rub Clean	Yes		
Valve Inlet Centres	150mm		
Valve Connection	15mm		
Valve Handle Material	Zinc		
Min Operating Pressure	0.5 Bar		
Max Operating Pressure	5 Bar		
Max Static Pressure	10 Bar		
Max Operating Temperature	85°C		
Thermostatic Safety Stop Setting	38°C		
Flow Restrictor	No		

Flow Rates

Pressure	0.2	0.5	1	3
L/min	_	5.6	8.2	14.6

All Pressures in Bar. All flow in L/Min. Dimensions supplied are nominal and subject to tolerance. Inclusion or restrictors (sold separately unless stated) will affect flow rate result.

Performance details are based on trials under test conditions and for guidance only. The Company reserves the right to change product specification without prior notice.

Certifications + Approvals

Flow Rate - 5.6 l/min



Tested at 0.5 Bar



Key Features + Benefits























Highlife Bathrooms







Keros_INST13217BB_TDS_V1

www.instinctproducts.co.uk

Technical Data Sheet | Shower

Keros Thermostatic Twin Outlet Bar Shower Mixer INST13217BB

330 G1/2" Ø20 Ø24 ø16 G1/2" G1/2" 150 307

Spares

Flow Control Cartridge INST13217FV
Thermostatic Cartridge INST13217TC