

Thurcroft Aluminium Cabinet INST06037, INST06038, INST06039



Key Features + Benefits

5 Years Guarantee	2 Years Guarantee Electrical Components	 USB Charging Socket	 Charging Socket	IP44 IP44 Rated	LED LED Lighting	CCT CCT Control Lighting
 Infrared Controls	 Heated Demister Pad	 Internal Shelves				

Specification

	INST06037 (Single Door)	INST06038 (Double Door)	INST06039 (Double Door)
Finish	Aluminium with mirrored sides	Aluminium with mirrored sides	Aluminium with mirrored sides
Dimensions	700(h) x 490(w) x 120(d) mm	700(h) x 590(w) x 120(d) mm	700(h) x 790(w) x 120(d) mm
Weight	20kg	20.3kg	25.2kg
Lighting Type	LED	LED	LED
Colour Changing Technology (CCT)	Yes	Yes	Yes
Switch Location	Right bottom	Right bottom	Right bottom
Surface/Recess Fitting	Surface	Surface	Surface
Carcass/Frame Construction Material	Aluminium	Aluminium	Aluminium
Carcass/Frame Finish	Aluminium	Aluminium	Aluminium
Number of Internal Shelves	Five	Five	Five
Shelves (Fixed/Adjustable)	Adjustable	Adjustable	Adjustable
Door Hinge Handing	Left hand	-	-
Glass Thickness	6mm	6mm	6mm

Features

Doors	Push-to-open, double sided mirror doors with demister pad
Lighting	Super bright LED lighting with colour changing, dimmable LED lighting, ambient & internal lighting, CCT (Correlated Colour Temperature) control

FAQs

Please see following pages


Certifications + Accreditations

Technical Data Sheet | Cabinets + Mirrors


www.instinctproducts.co.uk

Thurcroft Aluminium Cabinet INST06037, INST06038, INST06039


Single Door (INST06037)



Double Door (INST06038)



Double Door (INST06039)



Roper Rhodes

Brassmill Lane Trading Estate, Bath, BA1 3JF. Technical Support – Tel: 01225 303 900 Email: sales@roperrhodes.co.uk

All information on the data sheet is correct at the time of publication. All measurements are approximate and subject to standard tolerances.

Thurcroft Aluminium Cabinet INST06037, INST06038, INST06039

FAQs

	INST06037 (Single Door)	INST06038 (Double Door)	INST06039 (Double Door)
Important installation requirement	The product must be installed with a minimum distance of 150mm between the infrared sensor and an adjacent wall or obstruction to ensure correct function of the sensor.		
Internal Dimensions	470(h) x 663(w) x 98(d) mm	265(h) x 663(w) x 98(d) mm (either side)	365(h) x 663(w) x 98(d) mm (either side)
Shelf dimensions	206.5(h) x 90(w) x 5(d) mm	259(h) x 90(w) x 5(d) mm	359(h) x 90(w) x 5(d) mm
Max shelf spacing	70mm	70mm	70mm
Distance between door hinges	552mm	552mm	552mm
Individual door dimensions	687(h) x 467(w) x 6(d) mm	687(h) x 284.5(w) x 6(d) mm	687(h) x 384.5(w) x 6(d) mm
Max door opening angle	110° Max	110° Max	110° Max
Max depth with door open	570mm	387.5mm	487.5mm
Hanging bracket centres	-	-	-
What is the thickness of the mirror glass?	3 x 2mm	3 x 2mm	3 x 2mm
Is the cabinet IP44 rated?	Yes – suitable for use in bathroom zone 2		
What size fuse should I use?	Seek the advice of an electrician		
What is the total power consumption?	78W	108W	118W
Does the cabinet have an energy rating?	Yes, It has an energy rating of – F		
What is the colour of the light and the Kelvin rating?	2700-6400K	2700-6400K	2700-6400K
What is the Lumen of the LEDs?*	1950Lms	2490Lms	3270Lms
What is the wattage of the lights?	23W	28W	38W
Where is the IR sensor/rocker switch located?	Underneath – Right hand side		
Where is the shaver socket located?	In the centre column		
Can the LED lighting be replaced?	No**	No**	No**
Can the IR sensor be replaced?	Yes	Yes	Yes
What is the output of the demister pad?	25W	50W	50W
What are the dimensions of the demister pad?	200(h) x 300(w) mm	200(h) x 300(w) x 2(d) mm	200(h) x 300(w) x 2(d) mm
How do I turn on the demister pad?	The demister pad will turn on when the LEDs are turned on		
Are illuminated cabinets supplied with mains cable?	All illuminated cabinets are supplied with a removeable 500mm mains cable. There is ample storage for excess cable in the back of the unit.		

*The Lumen represents the output of the LED. This may vary depending on the diffuser material i.e., glass or acrylic.

**The LEDs are not replaceable to maintain the integrity of the product's resistance to moisture ingress.